



10W LED PAR 30 - WHITE

Description

Our 10W LED Par30 is great for indoor and outdoor applications where a rugged high-quality Par lamp is needed. Suitable for outdoor flood lights, signage, landscape lighting, and more. Made with CREE LEDs. Instant-on. Dimmable. While using only 10W, it's 85% more energy efficient than a 75W halogen. Available in 3 color temperatures and 3 beam spreads.



Features and Benefits

- IP Rating: IP54 (Damp Location)
- Material: Die-cast aluminum
- No mercury, lead or hazardous materials
- Certification: ETL, CE, RoHS
- Beam Angles: 24 deg/38 deg/90 deg
- Color Temperature: 2700K/4000K/5000K
- CRI >80
- Instant On
- Dimmable with most standard LED bulb dimmers
- Rated Lifetime: >50,000 hours
- 5 year warranty

Specifications

Power consumption 10W
 Input voltage 100-265VAC
 Weight..... 1.25lb
 Dimension..... 91mm * 90mm
 Operational Temp - 30°C~+45°C
 Efficacy 75 Lumens / Watt
 Base Type..... E26

| Model # | Color Temp | Lumen Output | Beam Spread | Wattage Equivalent |
|-------------------------------|------------|--------------|-------------|--------------------|
| LVL-CPAR30-10W-WW27-NFL-IP54 | 2700K | 650 | 24 deg | 75-100W Halogen |
| LVL-CPAR30-10W-NW40- NFL-IP54 | 4000K | 700 | 24 deg | 75-100W Halogen |
| LVL-CPAR30-10W-CW50- NFL-IP54 | 5000K | 750 | 24 deg | 75-100W Halogen |
| LVL-CPAR30-10W-WW27- FL-IP54 | 2700K | 650 | 38 deg | 75-100W Halogen |
| LVL-CPAR30-10W-NW40- FL-IP54 | 4000K | 700 | 38 deg | 75-100W Halogen |
| LVL-CPAR30-10W-CW50- FL-IP54 | 5000K | 750 | 38 deg | 75-100W Halogen |
| LVL-CPAR30-10W-WW27- WFL-IP54 | 2700K | 650 | 90 deg | 75-100W Halogen |
| LVL-CPAR30-10W-NW40- WFL-IP54 | 4000K | 700 | 90 deg | 75-100W Halogen |
| LVL-CPAR30-10W-CW50- WFL-IP54 | 5000K | 750 | 90 deg | 75-100W Halogen |